

Tenda O6 outdoor long range Point to Point CPE 5GHz 11AC 433Mbps, 16dB, 10km

Šifra:

Kategorija proizvoda: Bežično povezivanje

Proizvođač: Tenda

Cena: **12.341,00** rsd.



Dimension270*94.86*67.5mm

Frequency Range5GHz

Maximum wireless speed433Mbps

CPU ProcessorBroadcom 800MHz

GND Terminal1

Interface1*GE PoE/WAN/LAN port

Mode SwitchStation: The device only work in Station mode

Off: The device work on

AP/Station/Universal Repeater/WISP/Router mode

AP: The device only work in AP mode

ButtonReset: Press 10 seconds or more to restore to default settings

Bridge: Press 3 seconds and release it to bridge uplink AP

Antenna16dbi Directional Antenna

Antenna Beamwidth Horizontal: 30°

Vertical: 15°

Maximum Consumption9W

Lightning Protection6KV

Waterproof LevelIP64

LEDLAN,LED1,LED2,LED3

Power Supply24v 0.5A PoE Injector

Operating modeAP/Station/Universal Repeater/WISP/Router

Standard&ProtocolIEEE 802.11ac/n/a

Wireless SpeedEnable/Disable Wireless Radio

SSID Hidden

Wireless Client isolation

Sensitivity Threshold

WMM Capable
APSD Capable
Wireless Access Control
Wireless Client list
Wireless Security 64/128 WEP, WPA-PSK, WPA2-PSK, WPA&WPA2-PSK, WPA, WPA2
Transmit Power Adjustable power by 1dBm
Reception Sensitivity MCS0: -90dbm
MCS7: -72dbm
DHCP Server DHCP Server
Clients list
VPN Pass-through PPTP, L2TP
Ping Watchdog Support
Speed Test Support
Remote Web access Support
Schedule Reboot Support
Page Timeout Support
Dyndnsnoip, dyndns.org
Network Diagnoses Ping, Traceroute, Signal Scan
Management Tool Time&Date Setting
System Log
Firmware update
Backup/Restore Configuration
Username Management
Temperature Operating Temperature: -20? ~ 55?
Storage Temperature: -40? ~ 70?
Humidity Operating Humidity: 10%~90% non-condensing
Storage Humidity: 10%~90% non-condensing
Default Settings IP Address: 192.168.2.1
Login Username: admin
Login Password: admin
Certification FCC/CE/RoHS